

POINT OF USE

POINT-OF-USE ELECTRIC WATER HEATERS FEATURE DURABLE HEATING ELEMENT FOR INSTALLATION IN LIMITED SPACES

Efficiency:

- .93 EF for 30-gallon model (with pipe insulation)

Features:

- Rheem exclusive Magnesium anode rod provides long-lasting tank protection
- High Efficiency heating element
- Over-temperature protector cuts off power in excess temperature situations
- Automatic thermostat keeps water at desired temperature
- Wall mount kits available for easy installations
- Glass lined tank with Exclusive Rheemglas® tank lining that resists corrosion
- ASME rated temperature and pressure relief valve
- R-Foam insulation for superior heat retention
- Maximum tank working pressure of 150 PSI (10 BARS) Factory tested @ 300 PSI
- Available in 220V, 230V and 240V
- Available in 1.5, 2, 2.5, 3, 3.5, 4.5 and 6 Kw

Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts



| DESCRIPTION | | TESTING | ROUGHING IN DIMENSIONS (SHOWN IN INCHES) | | | | | APPROX. SHIP. WT (LBS) |
|-------------|--------------|----------|--|----------------------------|----------|--------------------------|----------------------------|------------------------|
| GAL. CAP. | MODEL NUMBER | | HEIGHT | HEIGHT TO HOT WATER OUTLET | DIAMETER | HEIGHT TO SIDE T&P VALVE | HEIGHT TO COLD WATER INLET | |
| 6 | RU85VP6-1 | UL / IEC | 15-1/4 | 12/1/2002 | 15-3/4 | 11/1/2002 | 4/1/2004 | 36 |
| 10 | RU85VP10 | UL / IEC | 23 | 20-1/2 | 15-3/4 | 19-1/2 | 4/1/2004 | 46 |
| 15 | RU85VP15 | UL / IEC | 24-1/5 | 22 | 17-3/4 | 21 | 4/1/2002 | 54 |
| 20 | RU85VP20 | UL / IEC | 25-1/4 | 22-3/4 | 19-3/4 | 21-3/4 | 5 | 69 |
| 30 | RU85VP30 | UL / IEC | 30 | 23 | 21-3/4 | 23 | 2/3/2004 | 91 |

*For double element, substitute "-2" suffix for "-1". Not available in 120 volt. Available with 2-wire (single phase) outlet only. (6000 watt max.).



RELY ON RUUD.™