Handwashing Portable Station

Mobile wash station with MiniTank brings comfortable handwashing to remote locations

Specifications

Handwashing Station with Electric Mini-Tank

Applications

- Construction Sites
- Education
- Foodservice
- Government

Performance Features

- Eemax MiniTank™ Electric Miniature Tank, 1.5-gallon with 15-amp plug for use in a 120-volt outlet
- Portable with two locking, all non-marring wheels make it easy to set up and deploy
- Sensor faucet for hands-free operation and integrated ASSE 1070 compliant mixing valve
- Stainless steel wash basin for easy cleaning
- Low-flow faucet at 0.15 GPM enables endless hot water on drain model
- Gray water tank model holds approximately 500, 20-second washes
- Constructed with lead-free components suitable for potable water

Product Specifications:

| Dimensions: | 41.75" x 61.25" x 25.75" | | | | |
|---------------------------|---|--|--|--|--|
| Heater Type: | Mini-Tank, 1.5 gallon Battery Sensor Faucet with below mount ASSE 1070 mixer 0.15 GPM | | | | |
| Faucet Type: | | | | | |
| Faucet Flow Rate: | | | | | |
| Number of Sinks: | 1 | | | | |
| Cabinet: | Rugged industrial strength plastic with powder coated steel panels, key lock door | | | | |
| Minimum Working Pressure: | 35 PSI | | | | |
| Maximum Working Pressure: | 150 PSI | | | | |

Special Design Service

Inquiries for units for unique applications are welcome. Call our Technical Service department at **1-800-543-6163**.





Suggested Specification

Portable handwashing station shall be an Eemax model number HPS14120____1MT. Eemax Handwashing portable station to be connected to a water supply and consists of a cart with stainless steel sink, low flow (0.15 GPM) sensor faucet, built in ASSE 1070 mixing valve and Eemax 1.5 gal MiniTank with T&P valve. Unit shall be Eemax or approved equal.

| D | Drain Model |
|---|-----------------------|
| W | Gray Water Tank Model |



Handwashing Portable Station

Mobile wash station with MiniTank water heater

Specifications

Handwashing Station with Electric Mini-Tank

| MODEL NUMBER | TYPE | kW | AMPS | MINITANK VOLUME | FAUCET FLOW RATE | WATER CONNECTION | WATER CONNECTION LOCATION | DRAIN CONNECTION | DRAIN LOCATION |
|--------------|------------|-----|------|--------------------|---------------------|----------------------|---------------------------|------------------|--------------------|
| VOLTS 120 | | | | | | | | | |
| HPS14120D1MT | Drain | 1.4 | 12 | 1.5 gallons | 0.15 GPM | 3/4" GHT or 3/4" NPT | Back of unit | 1-1/2" PVC stub | Back of unit |
| HPS14120W1MT | Gray Water | 1.4 | 12 | 1.5 gallons | 0.15 GPM | 3/4" GHT or 3/4" NPT | Left side of unit | 3/4" GHT | Right side of unit |



