

Packaged
AIR CONDITIONERS



The new degree of comfort.™

R-410A

R-410A HFC refrigerant

SLKL-B Series



R-410A
50Hz



Scroll compressors with internal line break overload and high-pressure protection



TXV or capillary tube refrigerant metering system on each circuit depending on models



High Pressure and Low Pressure/Loss of charge protection is standard on all models



Solid Core liquid line filter drier on each circuit



Easily removable filter, blower, electric heat, and control access panels permits prompt service



Outdoor coil protection with louver kit available through factory installed option or field installed



Externally mounted refrigerant gauge ports for easy service diagnostics



Forkable base rails for easy handling and lifting



Single point electrical connections

TECHNICAL DATA

SLKL-B		SLKL-B072NL	SLKL-B090NL	SLKL-B090NM	SLKL-B120NL	SLKL-B120NM
Rated Cooling Capacity @T1	Btu/hr	59500	70200	70200	97980	97980
Rated Cooling Capacity @T3	Btu/hr	53000	59000	59000	81000	81000
EER @T1	Btu/W-hr	11.2	11.9	11.9	11.8	11.8
EER @T3	Btu/W-hr	8.5	8.2	8.2	8.3	8.3
Rated Air Flow	CFM	1710	2400	2400	3000	3000
Unit Sizes	L (mm)	2089	2380	2380	2380	2380
	W (mm)	1221	1492	1492	1492	1492
	H (mm)	1216	1021	1021	1173	1173
Weight	kg	261	404	404	450	450
Refrigerant	R410A					

SLKL-B		SLKL-B151NL	SLKL-B151NM	SLKL-B180NL	SLKL-B240NM
Rated Cooling Capacity @T1	Btu/hr	124350	124350	161750	209250
Rated Cooling Capacity @T3	Btu/hr	108500	108500	134900	178500
EER @T1	Btu/W-hr	11.2	11.2	13.2	11.9
EER @T3	Btu/W-hr	8.1	8.1	9.1	8.3
Rated Air Flow	CFM	3500	3500	4525	6325
Unit Sizes	L (mm)	2380	2380	3177	3177
	W (mm)	1492	1492	2174	2174
	H (mm)	1118	1118	1448	1448
Weight	kg	575	575	756	871
Refrigerant	R410A				

T1 Condition: 27°C/19°C On-coil, 35°C ambient

T3 Condition: 29°C/19°C On-coil, 46°C ambient

Before proceeding with installation, refer to the installation instructions packaged with each model, as well as complying with all Federal, State, Provincial and local codes, regulation and practices.

RHEEM MANUFACTURING MEA FZE

Dubai Airport Freezone (DAFZA), UAE

"In keeping with its policy of continuous progress and product improvement, Rheem reserves the rights to make changes without notice."