

# Marathon® non-metallic electric water heaters are durable, lightweight and with the highest warranty period in the Market

#### **Non-metallic Tank Features**

- Seamless, blow-molded, polybutene tank – impervious to rust and corrosion
- Multiple layers of filament wound fiberglass give the tank unmatched strength
- Polyurethane insulation helps reduce energy consumption
- Recessed drain valve is out of the way brooms and scrubbers
- High temperature polysulfone dip tube
- Tough molded polyethylene outer shell resists dents, scratches, and salt air

### Efficiency

- .90 .94 EF
- Well insulated for reduced standby heat loss
- Pipe wrap energy saving kit included to achieve maximum energy savings

#### Performance

- FHR: 52-104 gallons, based on gallon capacity
- Recovery rate: 20 gallons GPH at a 90 degree riseaccidents.

### **Capacity & Dimensions**

• 40, 50, 85,105-Gallon tall models and a 50-gallon short

#### Easy Installation & Service

 Marathon's lightweight tank is easier to maneuver and position. Bowl shaped tank bottom drains completely.

#### Plus...

- Thermally fused upper element provides protection against dry-firing – titanium lower element for superior resistance to lime build-up
- Full-flow, brass drain valve
- Temperature and pressure relief valve
- Low Lead compliant
- Standard replacement parts

#### Warranty

• Up to 15 years on the tank and 6 years on parts

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy


êñ

ICC Code and all state energy efficiency performance criteria.



## Marathon

40 to 105-Gallon Capacities 240 Volt AC/Single Phase Electric



5-3/4

DESCRIPTION			FEATURES		ROUGHING IN DIMENSIONS (SHOWN IN INCHES)			
TYPE	GAL. CAP.	MODEL NUMBER	FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. 90°F RISE	TANK HEIGHT A	HEIGHT TO WATER CONN. B	DIAMETER C	APPROX. SHIP. WT (LBS)
Tall	30	MR30238	42	12	49	49-1/2	21-5/8	75
Tall	30	MR30245	42	20	49	49-1/2	21-5/8	75
Tall	40	MR40245	52	21	61-1/2	65-1/2	21-3/4	90
Tall	50	MR50245	61	21	62-3/4	66-3/4	23-1/2	100
Short	50	MSR50245	54	21	43-1/4	47-1/4	28-1/4	95
Tall	75	MHD75245	78	18.2 *	58-5/8	62-5/8	28-1/4	122
Tall	85	MHD85245	91	18.2 *	66-1/4	70-1/4	28-1/4	134

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Manufacturing MEA FZE

Dubai Airport Free Zone - Dubai, UAE

www.rheem-mea.com