



The new degree of comfort™

## Point-of-use electric water heaters feature a space-saving design for installation in limited spaces

### Efficiency

- .93 EF for 30-gallon model (with pipe insulation)

### Longer Life

- Rheem Exclusive Magnesium anode rod provides long-lasting tank protection

### Features

- High efficiency heating element
- Over-temperature protector cuts off power in excess temperature situations
- Automatic thermostat keeps water at desired temperature
- Wall mount kits available for easy installation
- Exclusive Rheemglas tank lining resists corrosion
- ASME rated temperature and pressure relief valve
- R-Foam Cyclopentane insulation for superior heat retention
- Maximum tank working pressure of 150 PSI (10 BARS)
- Factory tested @ 300 PSI

### Plus...

- These units are UL listed and comply with Underwriter's Laboratories Specifications 174 and IEC 60335-2-21

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHRAE standard 90, ICC Code and all state energy efficiency performance criteria.

### Warranty

- 6-Year limited tank and 2 years parts warranty



### POINT-OF-USE

123, 38, 57, 76 & 114-Liter Capacities  
 220, 230 & 240 Volt AC/Single Phase  
 50 Hz / 60 Hz  
 2-Wire Single Phase Electric  
 . Available in Simultaneous and Non-Simultaneous heating elements

MODEL NO.	WATTAGE @ 230 / 400 V
85VP6	1500 & 2000
85VP10	1500, 2000 & 3000
85VP15	1500, 2000, 3000 & 4500
85VP20	2000, 2500, 3000, 3500 & 4500
85VP30	2000, 3000, 4500 & 6000



DESCRIPTION		TESTING	ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					APPROX. SHIP. WT (LBS)
GAL. CAP.	MODEL NUMBER		HEIGHT	HEIGHT TO HOT WATER OUTLET	DIAMETER	HEIGHT TO SIDE T&P VALVE	HEIGHT TO COLD WATER INLET	
6	85VP6-1	UL / IEC	15-1/4	12/1/2002	15-3/4	11/1/2002	4/1/2004	36
10	85VP10	UL / IEC	23	20-1/2	15-3/4	19-1/2	4/1/2004	46
15	85VP15	UL / IEC	24-1/5	22	17-3/4	21	4/1/2002	54
20	85VP20	UL / IEC	25-1/4	22-3/4	19-3/4	21-3/4	5	69
30	85VP30	UL / IEC	30	23	21-3/4	23	2/3/2004	91

• 6 through 30 gallon models: 3/4" N.P.T. outlet, inlet, anode rod. T&P valve connections. Not available with 3 phase wiring.


Water heaters furnished standard with 230volt AC,2000 watt single element.

Special wiring options – a limited number of wiring options are available. Consult factory for price and availability.

**CONSTRUCTION DETAILS:** The cold water enters the tank a few inches from the bottom. Both hot and cold water lines may be connected directly to the water heater without special nipples or tees. The relief valve simply screws into the opening provided.

Energy Factor and Average Annual Operating Costs based on D.O.E.(Department of Energy) test procedures

\*\*Recovery = wattage / 2.42 x temp. rise °F.  
 Example: 4500W = 21 GPH  
 2.42 x 90°



In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Manufacturing MEA FZE  
 Dubai Airport Free Zone - Dubai, UAE  
 www.rheem-mea.com



INTEGRATED HOME COMFORT