

FURY DIRECT VENT

Fury™ direct vent vertical gas water heaters use outside air for combustion, offer longer venting options and a coaxial vent for easy installation



Performance:

- Well insulated for reduced stand-by heat loss
- FHR: 80 gallons for 50-gallon model and up to 66 gallons for 40-gallon model
- Recovery rate is up to 36.4 gallons at a 90 degree rise

Longer Life

- Patented magnesium rod with resistor protects the tank from rust
- Guardian System™ & Sensor
- Exclusive air/fuel shut-off device
- Maintenance free – no filter to clean
- Disables the heater in the presence of flammable vapor accumulation

Plus...

- Adjustable coaxial vent kit allows flexibility of installation and uses outside air for combustion and requires no electrical power
- Internal air tube for reduced footprint
- Brass drain valve and temperature and pressure relief valve are included
- Exclusive Rheemglas® tank lining to prolong tank life
- Heat saving flue baffle design
- Gas control and combination thermostat
- Piezo ignition



Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts

DESCRIPTION			FEATURES						DIMENSIONS					ALTITUDE RATING		ENERGY INFO.
TYPE	GAL. CAP.	MODEL NUMBER	GAS INPUT IN THOUS. BTU/H		RECOVERY IN G.P.H. 90° RISE		FIRST HOUR DEL. G.P.H.		DIAMETER	TANK HT.	VENT SIZE	HT. TO GAS CONN.	HT. TO SIDE T&P	SHIP. WT. (LBS)	FEET ABOVE SEA LEVEL NAT. AND LP	ENERGY FACTOR NAT.
			NAT.	LP	NAT.	LP	NAT.	LP								
T A L L	40	22DV40F-VX	36	30	36.4	30.3	66	65	19-3/4	59-3/4	5	14-1/4	51-5/8	155	7,700	0.59
	50	22DV50F-VX	36	32	36.4	32.3	80	80	21-3/4	59-1/2	5	14-1/4	52-1/2	165	7,700	0.59

