### **HEAVY & MEDIUM DUTY ELECTRIC**

# **Eclipse:** Non-metallic electric commercial water heaters are durable, lightweight and offer an exclusive 10-year limited warranty

## Eclipse models are more durable and energy efficient than any commercial electric water heaters ever made.

#### Eclipse<sup>™</sup> Benefits

With its exclusive 10-year limited tank warranty, the Eclipse family of 85 and 105-gallon water heaters offer a wide range of inputs and voltage options. It's non-metallic durable lightweight design make it easier to maneuver and position.

#### **Eclipse Features**

- 98% Thermal efficiency
- Foam insulated for reduced standby heat loss
- Recovery rate: Up to 99 gallons GPH at 100 degree rise
- 170° F Maximum temperature setting
- 85 and 105-Gallon capacities
- 12.4, 18 or 24 kW
- Voltage options: 208, 240, or 480
  VAC in either single phase or
  3-phase (277 VAC in single phase only)
- Element wattages: 3100, 4500 or 6000 in each of the four voltages. The elements are low watt density design (46, 67, 90 watts/sq. in.) with titanium sheath for superior protection
- Non-metallic tank no anode rods required
- High density polyethylene dent and scratch resistant jacket
- System Sentinel LED indicators are provided for each element to show when power is on

#### **Easy Installation & Service**

- Eclipse's lightweight tank is easier to maneuver and position
- Control circuit switch provided for dry fire protection during installation
- Bowl shaped tank bottom drains completely
- Recessed drain valve is out of the way of brooms and scrubbers
- Four titanium elements for resistance to lime build-up
- Full-port, full-flow, brass drain valve for faster draining
- Temperature and pressure relief valve at top of unit
- Water connections at the top of the tank are 1" swivel nuts
- A nipple is installed on the outlet (1" x 3" long)
- The inlet has a vacuum valve connected with a 1 x 1 x 3/4 tee and a 1" close nipple to the swivel

#### Warranty

• 10-Year limited tank warranty

#### **Eclipse Models**

DESCRIPTION				DIMENSIONS (INCHES)		
GAL. CAP.	MODEL NUMBER	INPUT KW	THERMAL EFF.	HEIGHT	WIDTH	SHIP WT. (LB.)
85	ME85	12.4, 18, 24	98%	66-1/4	28-1/4	170
105	ME105	12.4, 18, 24	98%	66-1/2	30-1/4	185





Download spec sheet from Rheem.com or ask for form RR102CE-6

