

POINT-OF-USE



Point-Of-Use electric water heaters feature a space- saving design for installation in limited spaces

Efficiency:

- .93 EF for 30-gallon model (with pipe insulation)

Features:

- Rheem exclusive Magnesium anode rod provides long-lasting tank protection
- High Efficiency heating element
- Over-temperature protector cuts off power in excess temperature situations
- Automatic thermostat keeps water at desired temperature
- Wall mount kits available for easy installations
- Exclusive Rheemglas tank lining resists corrosion
- ASME rated temperature and pressure relief valve
- R-Foam insulation for superior heat retention
- Maximum tank working pressure of 150 PSI (10 BARS) Factory tested @ 300 PSI
- Available in 220V, 230V and 240V
- Available in 1.5, 2, 2.5, 3, 3.5, 4.5 and 6 Kw



Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts

DESCRIPTION		TESTING	ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					APPROX. SHIP. WT (LBS)
GAL. CAP.	MODEL NUMBER		HEIGHT	HEIGHT TO HOT WATER OUTLET	DIAMETER	HEIGHT TO SIDE T&P VALVE	HEIGHT TO COLD WATER INLET	
6	85VP6-1	UL / IEC	15-1/4	12/1/2002	15-3/4	11/1/2002	4/1/2004	36
10	85VP10	UL / IEC	23	20-1/2	15-3/4	19-1/2	4/1/2004	46
15	85VP15	UL / IEC	24-1/5	22	17-3/4	21	4/1/2002	54
20	85VP20	UL / IEC	25-1/4	22-3/4	19-3/4	21-3/4	5	69
30	85VP30	UL / IEC	30	23	21-3/4	23	2/3/2004	91

*For double element, substitute “-2” suffix for “-1”. Not available in 120 volt. Available with 2-wire (single phase) outlet only. (6000 watt max.).



EP SERIES

Vertical and horizontal Point-Of-Use water heaters feature a space saving design for replacement and new construction applications

Features:

- High efficiency stainless steel heating element for added protection to prolong anode rod and tank life
- Factory installed heavy-duty wall mounting bracket(s) are included
- Over-temperature protector cuts off power in excess temperature situations
- Temperature indicator dial and diagnostic light
- All connections are conveniently located in the same area for easy installation
- ASME rated temperature and pressure relief valve
- Maximum tank working pressure of 150 PSI (10 BARS)
- Factory tested @ 300 PSI (20 BARS)
- R-Foam® insulation for superior heat retention
- ASME rated temperature and pressure relief valve
- Rheem exclusive magnesium anode rod
- Exclusive Rheemglas® tank lining resists corrosion
- Available in 220V, 230V and 240V - 1.5, 3 and 4.5 Kw



Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts

DESCRIPTION			DIMENSIONS (SHOWN IN MM)		INSULATION THICKNESS (MM)
LIT. CAP.	GAL. CAP.	MODEL NUMBER	CARTON DIMENSIONS	SHIPPING WEIGHT (KG)	
57	15	EP-15-V	473 x 424 x 699	25	22
76	20	EP-20-V	473 x 424 x 870	30	22
57	15	EP-15-H	473 x 424 x 699	25	22
76	20	EP-20-H	473 x 424 x 870	30	22

