

EP SERIES

Vertical and horizontal Point-Of-Use water heaters feature a space saving design for replacement and new construction applications

Features:

- High efficiency stainless steel heating element for added protection to prolong anode rod and tank life
- Factory installed heavy-duty wall mounting bracket(s) are included
- Over-temperature protector cuts off power in excess temperature situations
- Temperature indicator dial and diagnostic light
- All connections are conveniently located in the same area for easy installation
- ASME rated temperature and pressure relief valve
- Maximum tank working pressure of 150 PSI (10 BARS)
- Factory tested @ 300 PSI (20 BARS)
- R-Foam® insulation for superior heat retention
- ASME rated temperature and pressure relief valve
- Rheem exclusive magnesium anode rod
- Exclusive Rheemglas® tank lining resists corrosion
- Available in 220V, 230V and 240V - 1.5, 3 and 4.5 Kw



Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts

DESCRIPTION			DIMENSIONS (SHOWN IN MM)		INSULATION THICKNESS (MM)
LIT. CAP.	GAL. CAP.	MODEL NUMBER	CARTON DIMENSIONS	SHIPPING WEIGHT (KG)	
57	15	EP-15-V	473 x 424 x 699	25	22
76	20	EP-20-V	473 x 424 x 870	30	22
57	15	EP-15-H	473 x 424 x 699	25	22
76	20	EP-20-H	473 x 424 x 870	30	22

